Nextcloud

1. GID/UID Mapping für ZFS Passthrough
    1. https://pve.proxmox.com/wiki/Unprivileged_LXC_containers FIX für subuid/guid:

       https://lxc-users.linuxcontainers.narkive.com/KQxz7W3Z/uid-range-not-allowed
    2. FIX für "nogroup"-Problem

       https://forum.proxmox.com/threads/unable-to-map-to-www-data-user-in-container.49695/

       `pct mount CTID` `find /var/lib/lxc/CTID/rootfs -uid 100033 -exec chown 1005 '{}' \;` `find /var/lib/lxc/CTID/rootfs -gid 100033 -exec chgrp 1005 '{}' \;`
    3. Verzeichnis auf ZFS umsetzen
        1. Apache in CT deaktivieren (stop +disable)
        2. Original Nextcloudfiles ordener kopieren
        3. CT abschalten und mapping + mp0 mount auf ursprüngliches datenverzeichnis vornehmen
        4. CT anschalten kopie wieder in original ordner
        5. Enable + start apache
    4. `'skeletondirectory' => '',`
    5. Trusted domains -> reverse proxy ip eintragen
2. If you just want to remove the default skeleton (no files added on first launch), do the following:
    1. open config file with vi /app/config/config.php
    2. insert line 'skeletondirectory' => ''on a new line (i to enter insert mode)
    3. press esc, then :wq and <enter> to write and save

Revision #3
Created 3 September 2022 23:50:07 by TJN
Updated 3 May 2025 12:29:37 by TJN